THERMO KING

TRANE TECHNOLOGIES

Boost Charger

Protect liftgate operation from under-charged batteries and effortlessly extend runtime



Boost Charger

INTELLIGENT CHARGING TO MAXIMIZE UPTIME

- Senses and manages the charging voltage of an auxiliary battery to optimize health
- Temperature compensates charging to improve efficiency
- Temperature compensates to improve charging
- Selectable charging modes to meet any situation
- Fully sealed enclosure for mounting flexibility
- Available in both 20A and 30A versions



REQUIRED	PICK ONE	
20A Boost Charger **401333**	40' Harness **401335**	60' Harness **401336**
		
35A Boost Charger **401334**	40' Harness **401337**	60' Harness **401338**
		
Kit contains Boost Charger and connection wiring harness.	Multiple harness lengths available to accommodate installation needs.	

SPECIFICATIONS

- Available in 20Amp and 35Amp versions
- Input Voltage Range: 9.5 -16Vdc
- Max output current: 20A or 35A (model dependent)
- Can accommodate dual pole or single pole charging
- Operating Range: -40° to 85° C
- Dimensions: 7.5" x 5.5" x 2.5"
- Weight: 9lbs
- Warranty: 2 years

All Thermo King equipment is backed by the Thermo King dealer service network, with locations all across North America. To find a dealer in your area, go to **www.thermoking.com**.

57633-11-PL (02-26)
© 2026 Trane Technologies. All Rights Reserved.

TRANE TECHNOLOGIES